

Octet® QK^e System

Enhanced Quantitation and Kinetics Performance with Biosensor Re-racking

KEY FEATURES

- Increased sensitivity and dynamic range for protein quantitation
- Excellent signal resolution for measuring protein and peptide kinetics
- Greater operational cost savings with biosensor re-racking and regeneration



The Octet QK^e system is the enhanced-performance version of the first-generation Octet QK instrument from the Octet family of label-free biomolecular interaction analysis instruments. Two acquisition rate settings and a higher-performance spectrometer combine to provide greater sensitivity and a wider dynamic range for protein quantitation and kinetic analysis. In addition, biosensor re-racking provides enhanced assay flexibility and operational cost savings.

INCREASED SENSITIVITY AND DYNAMIC RANGE FOR PROTEIN QUANTITATION AND KINETICS

The Octet QK^e instrument contains the same high-performance spectrometer used in the Octet RED96 system. In addition, the Octet QK^e system provides a High Sensitivity acquisition rate setting for both quantitation and kinetics assays, allowing measurement of lower ranges of protein concentrations and smaller molecular weight analytes than was possible with the Octet QK system.

The Standard acquisition rate of 0.6 Hz with 5 averages per data point (1 data point per 1.6 seconds) is the default setting on the Octet QK^e system and equivalent to that on the Octet QK system. The High Sensitivity acquisition rate of 0.3 Hz (1 data point per 3.3 seconds) allows the software to perform 40 averages per data point to reduce noise and enhance signal to noise ratios, shown in Table 1, and gives the Octet QK^e system enhanced sensitivity for quantitation of proteins and peptides.

Kinetic analysis of proteins and peptides benefits from these Octet QK^e system enhancements over the Octet QK system in two ways:

- Lower molecular weight proteins and peptides can be detected and analyzed on the Octet QK^e system.
- The binding data for proteins or peptides at different concentrations can be better resolved on the Octet QK^e system, providing reliable measurement of kinetic constants.




FIGURE 1: Comparison of the binding of insulin (5.8 kDa) to biotinylated anti-insulin antibody anchored on Super Streptavidin biosensors on the Octet QK^e system (A), the Octet QK system (B), and the Octet RED system (C). The Octet QK^e system data was obtained using the Low acquisition rate setting of 0.3 Hz and 40 averages. The Octet RED system data was obtained using 5 Hz acquisition rate and 20 averages and the Octet QK system data was obtained using a 0.6 Hz acquisition rate and 5 averages.

System	Octet QK	Octet QK ^e		Octet RED
Setting	0.6 Hz, 5 avg	0.3 Hz, 40 avg	0.6 Hz, 5 avg	5 Hz, 20 avg
k_{on} (1/Ms)	1.51E+05	1.37E+05	1.08E+05	1.03E+05
k_{off} (1/s)	7.48E-02	8.00E-02	7.25E-02	6.56E-02
K_D (M)	4.95E-07	5.82E-07	6.71E-07	6.39E-07
S/N @ [0.5 K_D]	4.7	30.8	14.3	29.1

TABLE 1: Comparison of performance of the Octet QK, QK^e (at two different acquisition rates) and RED systems for the insulin (5.8 kDa)-anti insulin interaction.

Octet QK^e System Specifications*

Sample and Analysis	
Detection Technology	Bio-Layer Interferometry (BLI)
Biosensor Type	Disposable, single-use fiber optic biosensors with optional reuse by regeneration and/or re-racking
Information Provided	<ul style="list-style-type: none"> Kinetic and affinity analysis (k_{obs}, k_{ar}, k_{dr}, K_D) Concentration data analysis (no need for background subtraction) Epitope binning and cross-blocking matrices and trace overlays
Data Presentation	<ul style="list-style-type: none"> Plots displaying kinetic binding, equation fits, and residuals of fits Tabulated kinetic and quantitation data
Sample Types	Proteins, antibodies, peptides, media containing serum, buffers containing DMSO, periplasmic fractions, untreated cell culture supernatants, and crude cell lysates
Sample Plate	Standard 96-well, black, flat bottom microplate
Sample Volume	<ul style="list-style-type: none"> 180–220 μL/well (96-well microplate) Nondestructive testing, easily recovered
Orbital Flow Capacity	Static or 100–1500 rpm
Analysis Temperature Range	(Ambient + 4°C) – 40°C, 1°C increments

For more information about Pall ForteBio's Octet platform for label-free, real-time detection of biomolecular interactions, applications, and services, visit www.fortebio.com or contact us directly.

In comparison, the Octet QK384 system provides equivalent performance at greater throughput. The Octet HTX, RED96 and RED384 systems provide the best performance among the Octet family of instruments for quantitation and kinetic analysis, with the broadest dynamic range, greatest sensitivity, and ability to measure small molecule: protein binding and fast binding interactions.

MAKING QUALITY ANALYSIS AFFORDABLE

The Octet QK^e system provides re-racking and reuse of biosensors at the end of an experiment. Biosensor re-racking provides enhanced flexibility for loading ligands on biosensors and reduces operational costs by regenerating and re-using biosensors. Combined with superior data quality, the Octet QK^e system is a value-added alternative to other label-free instruments for your assays.

Quantitation and Kinetics

Throughput	Up to 8 assays in parallel; up to 96 assays per 96-well microplate
Analysis Time per Sample	<ul style="list-style-type: none"> hIgG quantitation in 2 minutes for 8 samples, \leq32 minutes for 96 samples Real-time kinetic analysis experiments from 5 minutes to 4 hours
Baseline Noise	<ul style="list-style-type: none"> \leq3 pm (RMS) at High Sensitivity acquisition rate \leq8 pm (RMS) at Standard acquisition rate
Quantitation Range for hIgG	1 μ g/mL to 700 μ g/mL at low rpm LOD of 0.05 μ g/mL at 1000 rpm

Physical Specs

Dimensions	18.6 in (H) x 17 in (D) x 20.8 in (W) 47 cm (H) x 43 cm (D) x 53 cm (W)
Weight	54 lb (24.5 kg)
Electrical Requirements	<ul style="list-style-type: none"> Mains: AC 100–240 V, 5.0–2.0 A, 50/60 Hz, single phase Power consumption: 120 W (240 W peak)
Safety Standards	<ul style="list-style-type: none"> CE, CSA

ORDERING INFORMATION

Part No.	UOM	Description
30-5046	System	Includes Octet QK ^e instrument, Octet software, desktop computer, LCD monitor, accessory kit, and one-year warranty

*Specifications are subject to change without notice.